



## COMFORT DEHUMIDIFIER TTR 56 E

*Convenient dry keeping without compressor, cooling agent or defrost pause*

The desiccant dehumidifier TTR 56 E is the ideal solution for the dry keeping of only temporarily heated or completely unheated holiday homes, weekend homes, yachts, sailing boats, basement rooms, garages and attics. For this dehumidifier reliably dries rooms of up to 12 m<sup>2</sup> even at low temperatures from 0 °C.

Due to its innovative desiccation technique the drying device needs neither a compressor nor cooling agent or defrost pauses, hence allowing a much more silent operation. With a dehumidification performance of up to 9 litres per day the TTR 56 E works extremely efficient already from a room temperature of 5 °C.

### **Drying of textiles included**

The TTR 56 E comes with three conveniently preselectable operating modes: Fully automatic, continuous operation and an extra mode specifically for the drying of textiles – especially advantageous when both the quick and convenient drying of wet laundry, clothing or carpets is in demand.

The equipment of the new desiccant dehumidifier is completed by a 24-hour timer function, filling level warning light indicating a full water tank, overflow protection with automatic switch-off and a washable air filter, which can easily be removed.

## Description

### Special features:

- Adsorption for non-stop dehumidification without defrosting
- Already 5° C room temperature very high dehumidification
- Three selectable modes with mode for drying textiles
- Level warning light with full water tank
- Overfill protection with auto switch off
- Washable air filter
- Manually adjustable air discharge
- Timer function
- Connection for external condensate drain

### Technical details of the TTR 56 E at a glance:

- Dehumidification performance max./24h: 8.5 litres
- Suitable for rooms\* with a size of up to 20 m<sup>2</sup>
- Suitable for room with a volume of up to 50 m<sup>3</sup>
- Operating range temperature:: 0°- 32°C
- Operating range relative humidity: 35 bis 90 % r.h.
- Air flow rate: max. 200 m<sup>3</sup>/h
- Functioning principle: desiccant dehumidifier
- Automatic defrost: elektronically
- Power supply: 220-244 V (50Hz)
- Power input max.: 0.78 kW
- Water tank (auto-off limit): 3.5 litres
- Noise level dB (A): 45
- Fan stages: 2
- Level warning light when water tank is full
- Manual adjustable blow out direction
- 24-hours timer-function
- Handle
- Connection for extern condensation drain
- Length: 200 mm
- Width: 445 mm
- Hight: 525 mm
- Weight: 8.5 kg